Care instructions

Cleaning and care of your WESSELER W-LINIE 2 glass wall

> This document contains both parts: sheets 1 and 2 cover care, sheets 3 and 4 operation. Both parts are also available separately for download.

AFTER INSTALLATION

The sealant needs to cure first. Please do not clean your glass wall thoroughly until at least two days after installation has been completed. Coarse building dust can be removed before that, dry or with clear water, without stressing the joints.

CLEANING THE GLASS

- **Standard glass cleaner** can be sprayed directly onto the glass. Clear water works just as well.
- **Use a soft, lint-free cloth,** ideally microfibre. Work in strips from top to bottom.
- **Do not leave standing water** on glass or profiles – always wipe the surfaces dry afterwards.
- **Clean both sides,** so streaks do not only show up in backlight.
- On glass with privacy film or lettering, use clear water only and work without pressure.

PROFILES, FRAMES AND FITTINGS

- **Powder-coated aluminium parts** should only be wiped with a damp, soft cloth and rubbed dry.
- **Handles and hinges** are wiped the same way; no polish and no oil on visible surfaces.
- **Keep the floor profile** free of dust and sand – both act like sandpaper when wiping.
- Clean seals and joints with water only, never with solvents.

PLEASE AVOID

- **No abrasive cleaners,** scouring pads, blades or scrapers – they permanently scratch glass and coating.
- **No aggressive cleaners** containing solvents, acids or alkalis.
- **No steam cleaner** and no pressure washer.
- Do not let cleaning agents soak into silicone joints.

Care instructions – special cases

Stubborn soiling, damage and who to contact

STUBBORN SOILING

- **Limescale:** remove with clear water and a soft cloth while still fresh. Do not scrape off dried rims.
- **Grease and fingerprints:** let glass cleaner act, then wipe off in one pass.
- **Adhesive residue and stickers:** soften carefully with warm water and lift with a fingernail or plastic spatula.
- **Paint, mortar, silicone:** do not remove these yourself – please get in touch before damage occurs.
- **Felt pen and markers:** try water first. Only then a mild agent, and only on glass, never on profiles.

WHAT TO EXPECT

- **Office and meeting rooms:** glass as needed, usually every one to two weeks.
- **Reception, retail, practice:** handle areas more often, glass surfaces at least weekly.
- **Profiles and floor track:** include them about once a month.
- **Check the fittings:** once or twice a year for smooth movement – see the operating instructions.

IF SOMETHING IS DAMAGED

Laminated safety glass does not break into sharp pieces; it stays bonded to the interlayer. A cracked pane is therefore not immediately dangerous, but it does need to be replaced. Secure the area, stop using the door and call us. Scratches in glass cannot be polished out – which is why avoiding blades and abrasives matters so much.

Operating instructions

Doors, fittings and everyday use – WESSELER W-LINIE 2

YOUR INSTALLATION AT A GLANCE

Fixed area:	laminated safety glass, pane to pane with a 2 mm butt joint, guided top and bottom in the wall and floor profile.
Door:	glass or timber door leaf in a system frame, held at the sides by posts.
Transom light:	above the door, closing the installation up to the ceiling.
Profiles:	aluminium, powder-coated in the chosen RAL colour.

OPERATING THE DOOR

- **Open and close gently.** Do not slam the door or throw it against the stop.
- **Always guide it by the handle,** never push on the glass edge or the leaf itself.
- **Double doors:** lock the passive leaf first, then close the active leaf.
- **Lock:** insert the key fully and turn without force. If it catches, press the door to slightly and turn again.
- **Use hold-open devices and door stops** only where they are fitted – never wedge the door open with objects.

IN EVERYDAY USE

- **Lean nothing against it:** no ladders, furniture, pallets or tools against glass or profiles.
- **Hang nothing from it:** fittings, handles and profiles are not designed to carry loads.
- **Do not hang on or lean against an open leaf** – not even briefly.
- **Keep the passage clear:** no cables, carpet edges or boxes within the swing area.
- **During work in the room** cover the glass surfaces – drilling dust, paint and sparks damage glass and coating.

Operating instructions – safety and faults

What you can do yourself and when we come out

SAFETY

- **Laminated safety glass:** does not break into sharp pieces but stays bonded to the interlayer. Still report a cracked pane at once and stop loading it.
- **Mark large glass areas:** where people walk briskly, a visibility strip or lettering at eye level helps.
- **Children:** doors are not play equipment – fingers do not belong in the gap between leaf and frame.
- **Escape routes:** doors in escape and rescue routes must be openable at all times without aids.
- **After an impact** check the pane in backlight: fine cracks at the edge are how damage starts.

IF SOMETHING STICKS

- **Door drags on the floor:** check the floor area for dirt and clean it. If that does not help, the hinge needs adjusting – please tell us.
- **Door does not close fully:** check whether something is caught in the rebate. Never force it shut.
- **Lock catches:** do not force the key. We will adjust the lock.
- **Handle feels loose:** do not tighten it yourself – the screw can stress the glass.
- **Creaking or whistling:** usually a draught or a seal. One call is enough and we will look at it.

ONCE A YEAR

Walk through the installation once a year: does every door move smoothly and close cleanly? Are handles and hinges firmly seated? Are the seals undamaged? Is the floor profile clear? Whatever you notice, we adjust during a service visit. Adjustment and replacement belong in professional hands – that is what keeps the installation sound.

QUESTIONS OR DAMAGE?

If something is damaged, a door sticks or you have a question about care, we help quickly and without fuss. Innenausbau Wesseler · Lise-Meitner-Straße 11a · 46325 Borken, Germany · Phone +49 2861 929753 · mw@mwesseler.com

> WESSELER W-LINIE 2 is our in-house type designation for this range. It is not a test or approval mark. These instructions apply to installations we manufactured and fitted ourselves.