# Care instructions

Cleaning and care of your WESSELER W-LINIE 2 glass wall

| 2 days | LSG | standard | none |
|---|---|---|---|
| after installation | laminated safety glass | glass cleaner | abrasive cleaners |

## AFTER INSTALLATION

The sealant needs to cure first. Please do not clean your glass wall thoroughly until at least two days after installation has been completed. Coarse building dust can be removed before that, dry or with clear water, without stressing the joints.

## CLEANING THE GLASS

- **Standard glass cleaner** can be sprayed directly onto the glass. Clear water works just as well.
- **Use a soft, lint-free cloth,** ideally microfibre. Work in strips from top to bottom.
- **Do not leave standing water** on glass or profiles – always wipe the surfaces dry afterwards.
- **Clean both sides,** so streaks do not only show up in backlight.
- On glass with privacy film or lettering, use clear water only and work without pressure.

## PROFILES, FRAMES AND FITTINGS

- **Powder-coated aluminium parts** should only be wiped with a damp, soft cloth and rubbed dry.
- **Handles and hinges** are wiped the same way; no polish and no oil on visible surfaces.
- **Keep the floor profile** free of dust and sand – both act like sandpaper when wiping.
- Clean seals and joints with water only, never with solvents.

## PLEASE AVOID

- **No abrasive cleaners,** scouring pads, blades or scrapers – they permanently scratch glass and coating.
- **No aggressive cleaners** containing solvents, acids or alkalis.
- **No steam cleaner** and no pressure washer.
- Do not let cleaning agents soak into silicone joints.

# Care instructions – special cases

Stubborn soiling, damage and who to contact

## STUBBORN SOILING

- **Limescale:** remove with clear water and a soft cloth while still fresh. Do not scrape off dried rims.
- **Grease and fingerprints:** let glass cleaner act, then wipe off in one pass.
- **Adhesive residue and stickers:** soften carefully with warm water and lift with a fingernail or plastic spatula.
- **Paint, mortar, silicone:** do not remove these yourself – please get in touch before damage occurs.
- **Felt pen and markers:** try water first. Only then a mild agent, and only on glass, never on profiles.

## WHAT TO EXPECT

- **Office and meeting rooms:** glass as needed, usually every one to two weeks.
- **Reception, retail, practice:** handle areas more often, glass surfaces at least weekly.
- **Profiles and floor track:** include them about once a month.
- **Check the fittings:** once or twice a year for smooth movement – see the operating instructions.

## IF SOMETHING IS DAMAGED

Laminated safety glass does not break into sharp pieces; it stays bonded to the interlayer. A cracked pane is therefore not immediately dangerous, but it does need to be replaced. Secure the area, stop using the door and call us. Scratches in glass cannot be polished out – which is why avoiding blades and abrasives matters so much.

## QUESTIONS OR DAMAGE?

If something is damaged, a door sticks or you have a question about care, we help quickly and without fuss. Innenausbau Wesseler · Lise-Meitner-Straße 11a · 46325 Borken, Germany · Phone +49 2861 929753 · mw@mwesseler.com

> WESSELER W-LINIE 2 is our in-house type designation for this range. It is not a test or approval mark. These instructions apply to installations we manufactured and fitted ourselves.